


EXTRA WIDE - TITAN XL for large diameter main sewers



Concrete DN 1000 / Concrete DN 1000



Approved seal onto
ANY pipe material
up to **2.5 bar!**



EXTRA WIDE - TITAN XL

Extra Wide Couplings TITAN XL are principally designed for joining large diameter pipes of size DN 1000 and greater.

The **300 mm width** of the coupling allows for greater tolerance in cutting of the pipe ends as well as providing for greater movement of the pipe ends due to settlement or thermal movement.

Whilst generally used on pipes over DN 1000 couplings are available to suit pipes from DN 300.

These couplings, because of their extra width can also be used to repair pipes, which are cracked or

have suffered local damage.

All couplings are manufactured to suit specific site requirements and can be produced in any diameter.

Uses:

- Connection of large diameter pipes.
- Repair of cracked or locally damaged pipes.
- Use where angular deflection at the joint is greater than that allowed by Canada Plus Type 2B.

EXTRA WIDE STANDARD COUPLINGS TITAN XL

REFERENCE	SIZE RANGE (MM)	WIDTH	BAR
MXL 310	285 - 310	300	2.5
MXL 320	290 - 320	300	2.5
MXL 335	310 - 335	300	2.5
MXL 350	325 - 350	300	2.5
MXL 360	335 - 360	300	2.5
MXL 385	355 - 385	300	2.5
MXL 410	385 - 410	300	2.5
MXL 430	400 - 430	300	2.5
MXL 445	415 - 445	300	2.5
MXL 465	435 - 465	300	2.5
MXL 495	465 - 495	300	2.5
MXL 510	480 - 510	300	2.5
MXL 525	495 - 525	300	2.5
MXL 545	515 - 545	300	2.5
MXL 560	530 - 560	300	2.5
MXL 570	540 - 570	300	2.5
MXL 600	570 - 600	300	2.5
MXL 620	590 - 620	300	2.5

EXTRA WIDE LARGE COUPLINGS TITAN XL

REFERENCE	SIZE RANGE (MM)	WIDTH	BAR
MXL 600	601 - 699	300	1.0
MXL 700	700 - 799	300	1.0
MXL 800	800 - 899	300	1.0
MXL 900	900 - 999	300	1.0
MXL 1000	1000 - 1099	300	0.6
MXL 1100	1100 - 1199	300	0.6
MXL 1200	1200 - 1299	300	0.6
MXL 1300	1300 - 1399	300	0.6
MXL 1400	1400 - 1499	300	-
MXL 1500	1500 - 1599	300	-
MXL 1600	1600 - 1699	300	-
MXL 1700	1700 - 1799	300	-
MXL 1800	1800 - 1899	300	-
MXL 1900	1900 - 1999	300	-
MXL 2000	2000 - 2099	300	-

Note: The coupling size ranges are an indication of size for ordering and availability purposes only. Couplings are manufactured to suit customer requirements.